


OVAL SIDE JACOB'S LADDER STEPS

Sides: 9" x 5" x 1-3/16" Rungs: 1-1/4" diameter Steps are 18" long overall




Ash or Oak

LADDER RUNGS

1-1/4" x 12" 1-1/4" x 14"

1-3/8" x 16"


1-3/8" × 18"



BOAT POLES

All Poles - Ash Hardwood

11/2" dia. x 8 ft. thru 16 ft. long with or without galvanized sharp or ball point hook



HATCH BOARDS

Constructed with welded steel end bands and thru bolts.

Specify length, width, thickness.



STANDING FIDS

24" x 4"

30'' x 4''

36" x 6"

HAND FIDS

6" x 1-3/8" 8" x 1-1/2"


10" x 1-1/2" 12" x 1-3/4"

14" x 1-3/4"

16" × 2"


18" x 2" 18" × 3"

20" × 2-1/4" 24" x 3"



PYROTECHNIC CHESTS

Constructed of 1/8" steel plate, welded, wood lined. Inside dimensions 24" long, 24" wide, 19" deep. Approximately 6-1/3 cubic feet. Chest primed with zinc chromate and finished with one coat of gray deck paint.



BOATSWAINS SEATS/CHAIRS

Cleats fastened to underside for added strength. Bored with 1" holes for rigging.


SIZE: 8" x 24" 10" x 24"

Chairs rigged, ready for use



WOOD PLUGS


For scuppers, cargo hose, etc. Specify top & bottom diameters.



HEARTS FOR FLAT STEPS

SIZE: 2" wide, 2-3/4" long, 1-3/16" thick

Grooved to match holes in 4-1/2" flat ladder steps



PILOT LADDER


Manufactured in accordance with U.S. Coast Guard and SOLAS regulations 160.017 and 163.003 which supersedes chapter 5, Reg. 17 of International Conference of Safety of Life at Sea (SOLAS).

Steps all 1-3/16" thick grooved for non-skid surface. Hearts and 70" spreaders standard.

All steps are pressure tested to 750 lbs. and branded with manufacturer's name and approval numbers.

All wood parts treated with Fed. Spec. TT-W-572 preservative.

Can be manufactured with rubber step segment.



ROUND RUNG LADDER

13

ROUND RUNGS: 1-1/4" x 14" 5/8" dia, manila rope Length as required