

DOUBLE LENS NAVIGATION LIGHTS

FOR USE ON ANY LENGTH VESSEL OVER 20 METERS (65.6 FT.) IN LENGTH.

FEATURES

CAST BRONZE.

COMPLETE WITH A PRE-WIRED MEDIUM PREFOCUS SOCKET AND TWO 3 FOOT LENGTHS OF 16/3-SO CABLE THROUGH WATERTIGHT TERMINAL TUBES.

WATERTIGHT ACCESS CAP FOR REBULBING AND CLEANING.

TWO PERKO CAT. No. 342 004 CLR, 120 VOLT BULBS INCLUDED.

IMPORTANT BULB DATA

To comply with the U.L. Standard 1104, the lights listed on this page must use PERKO Cat. No. 342 004 CLR bulb or 342 RS4 CLR bulb when a "Rough Service" bulb is required.

Height Overall Inches	Height Lens Inches	Weight Pounds	Mounting Bolt Size Inches
17-1/4	6-3/4	22-5/8	3/8

ORDERING INFORMATION

Description	Arc	Visibility Miles	Visibility Cat. No.
Red Side Light	112-1/2°	3	1164 RE0 PLB
Green Side Light	112-1/2°	3	1164 GE0 PLB
White Masthead Light	225°	6	1165 E00 PLB
White Stern Light*	135°	3	1166 E00 PLB
Yellow Towing Light	135°	3	1166 ME0 PLB
White All-Round Light*	360°	3	1167 E00 PLB
White All-Round Light**	360°	6	1167 HE0 PLB
Red All-Round Light	360°	3	1168 RE0 PLB
Green All-Round Light	360°	3	1168 GE0 PLB
Yellow All-Round Light	360°	3	1168 ME0 PLB

Special lights to meet local requirements are available upon request.

*These lights are supplied with a Gray Tinted Lens.

**For Great Lakes use.



Fig. 1164

SPARE PARTS ORDERING INFORMATION

- 1) Access Cap, O-Ring and Retainer, Cat. No. 1105 000 BLK.
- 2) O-Ring for Cap, Cat. No. 1119.
- 3) Lens Gasket, Cat. No. 1143.
- 4) Spare Lenses:
Red, Cat. No. 261 001 RED
Green, Cat. No. 261 001 GRN
White, Cat. No. 261 001 CLR
Gray, Cat. No. 261 001 GRY
Yellow, Cat. No. 261 001 YLW
- 5) Lens Retaining Clip with Bolt, Cat. No. 1133.
- 6) Dual Medium Prefocus Socket Assembly, Cat. No. 303.
- 7) Male Electrical Plug, Cat. No. 303 A00.
- 8) Female Electrical Receptical, Cat. No. 303 B00.

