


**NAVIGATION LIGHTS**



**Fig. 403-3**

**CAST BRONZE.  
COMPLETE WITH MEDIUM PREFOCUS SOCKET AND 120 VOLT BULB.**



Fig. No.	Height Overall Inches	Height Lens Inches	Tapped Pipe Size Inches	Weight Pounds	Visibility Miles
403	11-1/2	6-3/4	1	8-1/4	3
412	14	6-3/4	*	8-1/4	3



**Fig. 412**

	White	Red	Green	Yellow
Fig. No. 403	403 E03 PLB**	403 RE3 PLB	403 GE3 PLB	403 ME3 PLB
Fig. No. 412	412 E00 PLB**	412 RE0 PLB	412 GE0 PLB	412 ME0 PLB

\*Supplied with watertight terminal tube for 16/3-SO cable.

\*\*These Lights are Supplied with Gray Tinted Lenses.

**IMPORTANT BULB DATA**

To comply with U.L. Standard 1104, the lights listed on this page must use a PERKO Cat. No. 342 004 CLR bulb.

**SPARE PARTS ORDERING INFORMATION**

Spare Lenses:

Gray, Cat. No. 261 001 GRY.  
Red, Cat. No. 261 001 RED.  
Green, Cat. No. 261 001 GRN.  
Yellow, Cat. No. 261 001 YLW.

Spare Lens or Cover Gasket, Cat. No. 1143.  
Spare Medium Prefocus Socket, Cat. No. 347.



**Fig. 112A**



**CAST BRONZE. PLAIN OR CHROME PLATED.  
COMPLETE WITH DOUBLE CONTACT ELECTRICAL SOCKET  
FOR 12, 24, 32 OR 120 VOLTS. BULB NOT INCLUDED.**

Fig. No.	Height Overall Inches	Diameter Base Inches	Tapped Pipe Size Inches	Weight Pounds	Visibility Miles
112	8-3/4	3-1/8	----	2-1/2	2
309	6-1/2	----	1/2	2-1/4	2

Description	Plain Bronze	Chrome Plated Bronze	Description	Plain Bronze	Chrome Plated Bronze
	White All-Round	112 A00 PLB		112 A00 CHR	White All-Round
Red All-Round	112 RA0 PLB	112 RA0 CHR	Red All-Round	309 RA0 PLB	309 RA0 CHR
Green All-Round	112 GA0 PLB	112 GA0 CHR	Green All-Round	309 GA0 PLB	309 GA0 CHR
Yellow All-Round	112 MA0 PLB	112 MA0 CHR	Yellow All-Round	309 MA0 PLB	309 MA0 CHR

**IMPORTANT BULB DATA**

To comply with U.L. Standard 1104, the lights listed on this page must use a PERKO Cat. No. 374 bulb.

**SPARE PARTS ORDERING INFORMATION**

Spare Lenses:

Red, Cat. No. 106 000 RED.  
Green, Cat. No. 106 000 GRN.  
White, Cat. No. 106 000 WHT.  
Yellow, Cat. No. 106 000 YLW.

Required Bulbs:

12 Volts, Cat. No. 374 001 CLR.  
24 Volts, Cat. No. 374 002 CLR.  
32 Volts, Cat. No. 374 003 CLR.  
120 Volts, Cat. No. 374 004 CLR.

Spare Double Contact Bayonet Socket, Cat. No. 276 002.



**Fig. 309A**