


SLINGS WITH BASKET FITTINGS—TYPE II

WIDTH	PART NOS.			*RATED CAPACITY (lbs)	
	ALLOY STEEL	FORGED STEEL LOOSE PIN	FORGED ALUMINUM	VERTICAL	BASKET
2"	BHS1-X62	BHL1-X62	BHA1-X62	2200	4400
	BHS1-X92	BHL1-X92	BHA1-X92	3100	6200
	BHS2-X62	BHL2-X62	N/A	4400	8800
	BHS2-X92	BHL2-X92	N/A	6200	12400
	BHS4-X62	N/A	N/A	8800	17600
	BHS4-X92	N/A	N/A	12400	24800
3"	BHS1-X63	BHL1-X63	BHA1-X63	3300	6600
	BHS1-X93	BHL1-X93	BHA1-X93	4650	9300
	BHS2-X63	BHL2-X63	N/A	6600	13200
	BHS2-X93	BHL2-X93	N/A	9300	18600
	BHS4-X63	N/A	N/A	13200	26400
	BHS4-X93	N/A	N/A	18600	37200
4"	BHS1-X64	BHL1-X64	BHA1-X64	4400	8800
	BHS1-X94	BHL1-X94	BHA1-X94	6200	12400
	BHS2-X64	BHL2-X64	N/A	8200	16400
	BHS2-X94	N/A	N/A	11000	22000
	BHS4-X64	N/A	N/A	16400	32800
	BHS4-X94	N/A	N/A	22000	44000
5"	BHS1-X65	BHL1-X65	BHA1-X65	5500	11000
	BHS1-X95	BHL1-X95	BHA1-X95	7750	15500
	BHS2-X65	BHL2-X65	N/A	10250	20500
	BHS2-X95	BHL2-X95	N/A	13750	27500
	BHS4-X65	N/A	N/A	20500	41000
	BHS4-X95	N/A	N/A	27500	55000
6"	BHS1-X66	BHL1-X66	BHA1-X66	6600	13200
	BHS1-X96	BHL1-X96	BHA1-X96	9300	18600
	BHS2-X66	BHL2-X66	N/A	12300	24600
	BHS2-X96	BHL2-X96	N/A	16500	33000
	BHS4-X66	N/A	N/A	24600	49200
	BHS4-X96	N/A	N/A	33000	66000
8"	BHS1-X68	BHL1-X68	BHA1-X68	8800	17600
	BHS1-X98	BHL1-X98	N/A	12400	24800
	BHS2-X68	BHL2-X68	N/A	16400	32800
	BHS2-X98	N/A	N/A	22000	44000
	BHS4-X68	N/A	N/A	32800	65600
	BHS4-X98	N/A	N/A	44000	88000
10"	BHS1-X610	BHL1-X610	N/A	11000	22000
	BHS1-X910	BHL1-X910	N/A	15500	31000
	BHS2-X610	N/A	N/A	20500	41000
	BHS2-X910	N/A	N/A	27500	55000
12"	BHS1-X612	BHL1-X612	N/A	13200	26400
	BHS1-X912	BHL1-X912	N/A	18600	37200
	BHS2-X612	N/A	N/A	24600	49200
	BHS2-X912	N/A	N/A	33000	66000

*DO NOT EXCEED RATED CAPACITY


NOTE: Do not use slings with aluminum fittings (BHA) in applications where acids, alkalis or other corrosives are present.



BHS
(ALLOY STEEL)



BHL
(FORGED STEEL LOOSE PIN)



BHA (FORGED ALUMINUM)

Basket End Fittings (BHS, BHA, BHL)

Eyes are metal instead of tapered fabric. Fittings available in Alloy steel, Forged Aluminum or Forged steel loose pin types.

For use in basket hitch only Available in Nylon or Polyester Webbing.

For Polyester Webbing add the letter "P" to the Part No. (Example—BHS1-X62P)

End Fitting specs. on page 13