

# Swivel Hoist Rings

- 100% individually proof tested to 2-1/2 times the Working Load Limit with certification and statistically magnetic particle inspected. (Can be furnished 100% magnetic particle inspected when requested at time of order).
- Individually packaged along with proper application instructions and warning information.
- 360° swivel and 180° pivot.
- Fatigue rated to 20,000 cycles at 1-1/2 times the Working Load Limit.
- Bolt is secured with retaining ring (Patented). Replacement kit available.
- Bolt is individually Proof Tested.
- Multiple bolt length available to meet specific application requirements.



**HR-125  
UNC THREADED**



**HR-125M  
METRIC THREADED**

### U.N.C. THREADS

Working Load Limit (lbs.)	Bolt Size (in.)	HR-125 Stock No.	1 - 20 Pcs. Price Each	21-45 Pcs. Price Each	46 - 100 Pcs. Price Each	Weight Each (lbs.)
800	5/16-18x1.50	1016887				.43
1000	3/8 -16x1.50	1016898				.38
2500	1/2 -13x2.00	1016909				2.50
2500	1/2 -13x2.50	1016912				2.50
4000	5/8 -11x2.00	1016920				2.55
4000	5/8 -11x2.75	1016924				2.70
5000	3/4 -10x2.25	1016931				2.65
5000	3/4 -10x2.75	1016935				3.00
7000	3/4 -10x2.75	1016942				7.00
7000	3/4 -10x3.50	1016946				7.00
8000	7/8 -9x2.75	1016953				7.00
8000	7/8 -9x3.50	1016957				7.00
10000	1 -8x3.00	1016964				7.50
10000	1 -8x4.00	1016969				7.50
15000	1 1/4 -7x4.50	1016975				14.75
24000	1 1/2 -6x6.50	1016986				33.00
30000	2 -4 1/2x6.50	1016997				36.00


### METRIC THREADED

Working Load Limit (kg)		Bolt Size (mm)	HR-125M Stock No.	1 - 20 Pcs. Price Each	21 - 45 Pcs. Price Each	46 - 100 Pcs. Price Each	Weight Each (kg)
At a 5:1 Design Factor	At a 4:1 Design Factor						
400	500	M 8 x 1.25 x 40	1016602				.17
450	550	M 10 x 1.50 x 40	1016613				.17
1050	1300	M 12 x 1.75 x 50	1016624				1.13
1900	2400	M 16 x 2.00 x 60	1016635				1.22
2150	2700	M 20 x 2.50 x 65	1016644				1.36
3000	3750	M 20 x 2.50 x 75	1016657				3.40
4200	5250	M 24 x 3.00 x 80	1016668				3.40
7000	8750	M 30 x 3.50 x 120	1016679				6.35
11000	13750	M 36 x 4.00 x 150	1016690				14.97
12500	15600	M 42 x 4.50 x 160	1016701				16.33
13500	16900	M 48 x 5.00 x 160	1016712				16.33

### HOIST RING CHAIN CONNECTOR

Working Load Limit (lbs.)*	Bolt Size (in.)	HR-125C Stock No.	1 - 7 Price Each	8 & Up Price Each	Weight Each (lbs.)
4500	5/8 - 11 x 2.00	1067492			2.1
4500	5/8 - 11 x 2.75	1067494			2.2
7100	3/4 - 10 x 2.75	1067500			5.5
7100	3/4 - 10 x 3.50	1067502			5.6
12000	1 - 8 x 3.00	1067509			6.2
12000	1 - 8 x 4.00	1067511			6.4
18100	1-1/4 - 7 x 4.50	1067518			13.1

Based on 4:1 design factor.



**HR-125C  
CHAIN CONNECTOR**