



# Western<sup>®</sup> Manila Rope Snatch Blocks

**SEE APPLICATION AND WARNING INFORMATION**

## DROP LINK & SELF LOCKING


- All styles have drop forged heads and links.
- Edges of shell are rounded to protect rope.
- Steel sleeve over center pin gives a bearing surface of larger diameter. The sleeve is held tightly between the plates and makes blocks extremely rigid



Block Size (in.)	Fitting	Stock No.						
		Drop Link					Self-Locking	
		Wood Shell			Steel Shell		Wood Shell	Steel Shell
		385-C Galv.	385-R Galv.	385-B Galv.	390-C Jap.	390-B Galv.	386-B Galv.	391-B Galv.
6	T	723612	723818	724014	733601	734012	729019	739017
8	T	723658	723854	724050	733647	734058	729055	739053
10	T	723676	723872	724078	733665	734076	729073	739071
12	T	723694	723890	724096	733683	734094	729091	739099
6	J	—	—	722212	—	732210	727217	737215
8	J	—	—	722258	—	732256	727253	737251
10	J	—	—	722276	—	732274	727271	737279
12	J	—	—	722294	—	732292	727299	737297
6	G	—	—	722819	—	732817	727814	737812
8	G	—	—	722855	—	732853	727850	737858
10	G	—	—	722873	—	732871	727878	737876
12	G	—	—	722891	—	732899	727896	737894

Bearing Code: B — Bronze Bushed, Self Lubricating, C — Common Iron, R — Roller Bearing.

### DROP LINK



T-385-B


Block Size (in.)	Sheave Size (in.)			Manila Rope Size (in.)	Working Load Limit * (lbs.)	Weight Each (lbs.)
	Outside Diam.	Rim Thickness	Bearing Diameter			
6	3.00	1.13	.75	3/4 - 7/8	2400	7
8	4.50	1.38	.88	1 - 1 1/8	4800	13
10	5.75	1.88	1.00	1 1/4	6600	25
12	6.75	2.13	1.00	1 1/2	7600	34

\* Ultimate Load is 4 times the Working Load Limit.



T-390-B


### SELF LOCKING



T-386-B

Block Size (in.)	Sheave Size (in.)			Manila Rope Size (in.)	Working Load Limit * (lbs.)	Weight Each (lbs.)
	Outside Diam.	Rim Thickness	Bearing Diameter			
6	3.00	1.13	.75	3/4 - 7/8	3000	8
8	4.50	1.38	.88	1 - 1 1/8	5000	15
10	5.75	1.88	1.00	1 1/4	8000	28
12	6.75	2.13	1.00	1 1/2	10000	38

\* Ultimate load is 4 times the Working Load Limit.



T-391-B