


# COMPOSITE

## BULK REELS

**Twisted Extralene 3/8" - 4" Dia.  
Polyester &  
Polypropylene  
Composite  
(White with  
Orange Tracer)**

- Good Knot Retention
- Good Dielectric Properties
- Good for Safety Lines



Item No.	Size	Min. Break	Reel Wgt.
05461	3/8" x 300'	2,430	10.80
05462	3/8" x 600'	2,430	21.60
05463	3/8" x 1200'	2,430	43.20
05483	1/2" x 300'	3,960	19.50
05466	1/2" x 600'	3,960	39.00
05467	1/2" x 1200'	3,960	78.00
05486	5/8" x 300'	5,760	28.50
05468	5/8" x 600'	5,760	57.00
05469	5/8" x 1200'	5,760	114.00
05470	3/4" x 600'	7,560	75.00
05471	3/4" x 1200'	7,560	150.00
05472	7/8" x 600'	10,800	108.00
05473	7/8" x 1200'	10,800	216.00
05474	1" x 600'	13,100	130.80
05475	1" x 1200'	13,100	261.60
R8261	1-1/8" x 600'	17,400	174.00
R8263	1-1/4" x 600'	19,800	200.40
R2942	1-5/16" x 600'	21,200	213.60
R8265	1-1/2" x 600'	26,800	270.00
R8266	1-5/8" x 600'	32,400	333.00
R8067	1-3/4" x 600'	38,800	399.00
R8268	2" x 600'	46,800	468.00
R8269	2-1/4" x 600'	62,000	630.00
R8270	2-1/2" x 600'	72,000	732.00
R8271	2-5/8" x 600'	81,000	828.00
*	2-7/8" x 600'	91,000	930.00
*	3" x 600'	103,000	1044.00
R8024	3-1/4" x 600'	123,000	1260.00
*	3-1/2" x 600'	146,000	1536.00
*	4" x 600'	171,000	1800.00

\* Request item number for sizes above 1" diameter and for specific colors, putups, and special lengths. Minimum runs may be required.

### Barrier Rope (International Orange) (#8) 1/4" Dia.

Item No.	Size	Min. Break	Reel Wgt.
05236	(#8) 1/4" x 1000'	990	9.10

## PRO-MASTER™



**3-Strand  
Spun and Filament  
Polyester Jacket  
Fibers Covering  
Polyolefin Core  
Fibers.**

A firm, balanced three-strand construction with superior hand and lock-grip holding capability. This product offers flexibility but keeps its shape under heavy use. The combination of spun and filament polyester develop a rope with low stretch and excellent knot holding. The construction's firmness virtually eliminates the hockling tendency of standard lay three-strand even in long

continuous lengths. Pro-Master™ is a superior rope for rigging due to its light weight, low stretch, excellent grip and high strength.

### 3-STRAND PRO-MASTER

SIZE				WEIGHT		AVERAGE STRENGTH	
Dia. Inch	Dia. mm	Circ. Inch	Circ. mm	Lbs per 100 Ft.	Kg per 100 M	Lbs	Kg
1/2"	12	1-1/2"	36	5.7	8.5	5,800	2,631
5/8"	16	2"	48	9.5	14.1	8,200	3,720
3/4"	18	2-1/4"	54	12.5	18.6	10,800	4,899
7/8"	22	2-3/4"	66	18.0	26.8	15,500	7,031
1"	24	3"	72	22.0	32.7	18,700	8,482

Specific Gravity: ..... 1.24

Elastic Elongation at Percentage of Break Strength:

10%	20%	30%
2.0	3.2	3.9

Water Absorption

Fiber: ..... 1-2%

#### MINIMUM STRENGTH

Lbs	Kg
5,220	2,368
7,380	3,348
9,720	4,409
13,950	6,328
16,830	7,634

### CHARACTERISTICS

Stays firm and gives excellent hold/grip  
High strength and low stretch

Excellent chemical and ultraviolet resistance  
Balanced, hockle-resistant construction

### APPLICATIONS

Vertical Life Lines  
Stage Counter  
Weight Rope

Arborist Rigging Line  
Hand and Block Lines

Fiber Content: ..... Polyester and Polyolefin fiber