

THE PRODUCTS LISTED BELOW ARE AVAILABLE AS FOLLOWS:

THICKNESS: 1/32" thru 1" — 1mm thru 25mm • WIDTH: 36", 1m, and 48" and slabs to 3"

NEOPRENE SHEET RUBBER ASTM D-2000 (SAE 3200) 1BC, 510, 610 AND 710

| Color & Finish | Durometer Shore A ±5 | Average Tensile lbs. PSI | Average Elongation% | Temp. Range | Oil Resist. | Branding None | Wt. Per Sq.Yd. | Specific Gravity |
|----------------|----------------------|--------------------------|---------------------|----------------|-------------|------------------------------|----------------|------------------|
| Black/Smooth | 50, 60, 70 | 1000 | 300 | -20F to + 212F | Good | Packaging Reinforced Plastic | 1/8 – 8.6 | 1.60 |

NITRILE (BUNA-N) SHEET RUBBER ASTM D-2000 (SAE J200) 1BF 610

| Color & Finish | Durometer Shore A ±5 | Average Tensile lbs. PSI | Average Elongation% | Temp. Range | Oil Resist. | Branding None | Wt. Per Sq.Yd. | Specific Gravity |
|----------------|----------------------|--------------------------|---------------------|----------------|-------------|------------------------------|----------------|------------------|
| Black/Smooth | 60 | 1000 | 300 | -20F to + 212F | Good | Packaging Reinforced Plastic | 1/8 – 9.1 | 1.56 |

WHITE NITRILE (BUNA-N) F.D.A. APPROVED INGREDIENTS 1BF 610

| Color & Finish | Durometer Shore A ±5 | Average Tensile lbs. PSI | Average Elongation% | Temp. Range | Oil Resist. | Branding None | Wt. Per Sq.Yd. | Specific Gravity |
|----------------|----------------------|--------------------------|---------------------|----------------|-------------|------------------------------|----------------|------------------|
| White/Smooth | 60 | 1000 | 300 | -20F to + 212F | Good | Packaging Reinforced Plastic | 1/8 – 9.1 | 1.5 |

BUTYL SHEET RUBBER

| Color & Finish | Durometer Shore A ±5 | Average Tensile lbs. PSI | Average Elongation% | Temp. Range | Oil Resist. | Branding None | Wt. Per Sq.Yd. | Specific Gravity |
|----------------|----------------------|--------------------------|---------------------|----------------|-------------|------------------------------|----------------|------------------|
| Black/Smooth | 60 | 1500 | 300 | -40F to + 225F | NONE | Packaging Reinforced Plastic | 1/8 – 8.6 | 1.47 |

EPDM SHEET RUBBER ASTM D-2000 (SAE J200) 1BA610

| Color & Finish | Durometer Shore A ±5 | Average Tensile lbs. PSI | Average Elongation% | Temp. Range | Oil Resist. | Branding None | Wt. Per Sq.Yd. | Specific Gravity |
|----------------|----------------------|--------------------------|---------------------|----------------|-------------|------------------------------|----------------|------------------|
| Black/Smooth | 60 | 1000 | 350 | -40F to + 220F | NONE | Packaging Reinforced Plastic | 1/8 – 8.4 | 1.44 |

HYPALON SHEET RUBBER ASTM D-2000 1CE615

| Color & Finish | Durometer Shore A ±5 | Average Tensile lbs. PSI | Average Elongation% | Temp. Range | Oil Resist. | Branding None | Wt. Per Sq.Yd. | Specific Gravity |
|----------------|----------------------|--------------------------|---------------------|----------------|-------------|------------------------------|----------------|------------------|
| Black/Smooth | 60 | 1500 | 400 | -20F to + 212F | Good | Packaging Reinforced Plastic | 1/8 – 9.2 | 1.58 |

RED SBR SHEET RUBBER ASTM D-1330-66 CLASS 1

| Color & Finish | Durometer Shore A ±5 | Average Tensile lbs. PSI | Average Elongation% | Temp. Range | Oil Resist. | Branding None | Wt. Per Sq.Yd. | Specific Gravity |
|----------------|----------------------|--------------------------|---------------------|----------------|-------------|------------------------------|----------------|------------------|
| Red/Smooth | 75 | 700 | 200 | -20F to + 212F | Good | Packaging Reinforced Plastic | 1/8 – 11.0 | 1.88 |

CLOTH— INSERTED SHEET RUBBER SBR HH-P-151, CLASS 1

| Color & Finish | Durometer Shore A ±5 | Average Tensile lbs. PSI | Elongation | Temp Range | Oil Resist. | Branding None | Fabric Cotton | |
|----------------|----------------------|--------------------------|------------|----------------|-------------|---------------|---------------|-----------------------------|
| Black/Smooth | 75 | 1/8" 100# GRAB | 1/8" 8% | -20F to + 170F | NO | NO | YES | W C per sq. yd. 1/8 – 11 |

T.R. DIAPHGRAM/C.I. SHEET RUBBER NEOPRENE – High Strength, Tear Resistant, Non Wicking

| Color & Finish | Durometer Shore A ±5 | Average Tensile lbs. PSI | Break Strength Fabric | Temp Range | Oil Resist. | Branding None | Fabric Nylon | |
|----------------|----------------------|--------------------------|-----------------------|----------------|-------------|---------------|--------------|----------------------------|
| Black/Smooth | 75 | 1500 lbs./sq. in. | 1400 lbs./ per ply | -20F to + 212F | YES | NO | YES | W C per sq. yd 1/8 – 11 |

T.R. DIAPHGRAM/C.I. SHEET RUBBER BUNA-N- High Strength, Tear Resistant, Non Wicking

| Color & Finish | Durometer Shore A ±5 | Average Tensile compound | Break Strength | Temp Range | Oil Resist. | Branding None | Fabric Nylon | |
|----------------|----------------------|--------------------------|-------------------|----------------|-------------|---------------|--------------|----------------------------|
| Black/Smooth | 75 | 1000 lbs./sq. in. | 1400 lbs./per ply | -20F to + 212F | YES | NO | YES | W C per sq. yd 1/8 – 11 |

PURE GUM NATURAL RUBBER – Floating Stock ASTM-D-75E, SAE J200, 1AA 420, Mil-R-3065 RN 420AB

| Color & Finish | Durometer Shore A ±5 | Average Tensile lbs. PSI | Average Elongation | Temp Range | Oil Resist. | Branding None | Specific Gravity |
|----------------|----------------------|--------------------------|--------------------|----------------|-------------|------------------------------|------------------|
| Tan/Smooth | 40 | 3000 | 600% | -20F to + 140F | NONE | Packaging Reinforced Plastic | 1.0 |

VITON SHEET RUBBER 1,000 lb. Tensile

| Color & Finish | Durometer Shore A | Average Elongation | Temp Range | Oil Resist. | Branding None | Wt. Per Sq. Yd. |
|----------------|-------------------|--------------------|----------------|-------------|------------------------------|-----------------|
| Black/Smooth | 60-70 | 200% | -15F to + 400F | EXCELLENT | Packaging Reinforced Plastic | 1/8" 10.74# |