

**OSBORNE NO. G1**

For best results in setting No. G1 grommets and washers use an Osborne No. 500 hole punch and an Osborne No. 216 setting die with corresponding sizes.



**BRASS PLAIN RIM GROMMETS AND WASHERS**

Size No.	Diameter of hole when set (inches)	Weight per gross (lbs) (oz)		UPC No.
00	3/16	-	2	13012
0	1/4	-	5	13014
1	9/32	-	8	13016
2	3/8	-	12	13018
3	7/16	1	2	13020
4	1/2	1	8	13022
5	5/8	1	12	13024
6	13/16	6	-	13026

**OSBORNE NO. N1**

Same specification as Osborne No. G1 except Osborne No. N1 is nickel plated brass.



**NICKEL PLATED BRASS PLAIN RIM GROMMETS AND WASHERS**

Size No.	Diameter of hole when set (inches)	Weight per gross (lbs) (oz)		UPC No.
00	3/16	-	2	13112
0	1/4	-	5	13114
1	9/32	-	8	13116
2	3/8	-	12	13118
3	7/16	1	2	13120
4	1/2	1	8	13122
5	5/8	1	12	13124
6	13/16	6	-	13126

**OSBORNE NO. G2**

For best results in setting No. G2 spur washers and grommets use an Osborne No. 500 hole punch and an Osborne No. 217 setting die.



**BRASS ROLLED RIM GROMMETS AND SPUR WASHERS**

Size No.	Diameter of hole when set (inches)	Weight per gross (lbs) (oz)		UPC No.	Size No.	Diameter of hole when set (inches)	Weight per gross (lbs) (oz)		UPC No.
0	1/4	-	13	13044	5	5/8	3	8	13054
1	5/16	-	18	13046	6	3/4	5	10	13056
2	3/8	1	10	13048	7	15/16	5	10	13058
3	7/16	2	4	13050	8	1 1/16	8	2	13060
4	9/16	2	4	13052					

**OSBORNE NO. N2**

Same specification as Osborne No. G2 except Osborne No. N2 is nickel plated brass.



**NICKEL PLATED ROLLED RIM GROMMETS AND SPUR WASHERS**

Size No.	Diameter of hole when set (inches)	Weight per gross (lbs) (oz)		UPC No.	Size No.	Diameter of hole when set (inches)	Weight per gross (lbs) (oz)		UPC No.
0	1/4	-	13	13144	5	5/8	3	8	13154
1	5/16	-	18	13146	6	3/4	5	10	13156
2	3/8	1	10	13148	7	15/16	5	10	13158
3	7/16	2	4	13150	8	1 1/16	8	2	13160
4	9/16	2	4	13152					